
















# Comprehensive List of Dies

PROFESSIONAL GRADE COAXIAL DIES		
Photograph	Description	Part Number
	HEX CAVITY: .610"	RFA-4009-01
	HEX CAVITIES: .042", .068", .255"	RFA-4009-03
	HEX CAVITIES: .068", .130", .178"	RFA-4009-04
	HEX CAVITIES: .100", .118", .429"	RFA-4009-05
	HEX CAVITIES: .068", .100", .213"	RFA-4009-06

COMMERCIAL GRADE MODULAR DIES		
Photograph	Description	Part Number
	For non-insulated terminals AWG 22-8	RFA-4005-21
	For non-insulated flag terminals from 0.5 to 2.5 sq.mm. AWG 22-18, 16-14	RFA-4005-22
	For cord end terminals from 0.5 to 10 sq.mm. AWG 22-8	RFA-4005-23
	For insulated terminals from 0.5 to 6 sq.mm. AWG 22-18, 16-14, 12-10	RFA-4005-24
	For non-insulated open barrel terminal from 0.5 to 6 sq.mm. AWG 22-18, 16-14, 12-10	RFA-4005-25
	For non-insulated terminals and cable lugs from 1.5 to 6 sq.mm. AWG 22-18, 16-14, 12-10	RFA-4005-26
	For non-insulated terminals DIN 46234 from 0.5 to 10 sq.mm. AWG 22-18, 16-14, 12-10, & 8	RFA-4005-27

COMMERCIAL GRADE COAXIAL DIES		
	RG-58/U, RG-59/U, RG-142/U, RG-223/U, RG-400/U, RG-8X, PROFLEX AND VARIOUS VIDEO CABLES, CAVITY DIMENSIONS: .052", .068", .100", .213" AND .255".	RFA-4005-01
	RG-8/U, RG-213/U, RG-214/U, AND BELDEN 9913 CABLES, CAVITY DIMENSIONS: .100", .128" & .429". THE .128" CAVITY CRIMPS THE CENTER PIN ON BELDEN 9913 CABLE.	RFA-4005-02
	.228", .068", .305", for RG-58/U, RG-59/U, RG-62/U and Cambridge Connectors Series CP-88 & CP-89	RFA-4005-04
	.155", .184", .215"	RFA-4005-05
	.255", .324", .354" for RG-59/U, RG-6/U, and F-Type (CATV) Coax Connectors	RFA-4005-06
	.213", .178", .068", .042", for RG-58/U, RG-174/U, RG-316/U Coax Connectors (RFI Cable Groups B and C)	RFA-4005-07
	.324", .255", .068", .042", for RG-59/U and Belden 8281 Coax Cable (RFI Cable Groups D and G)	RFA-4005-08
	.178", .128", .068", for RG-174/U, RG-188/U, RG-316/U and Mini 59/U Coax Connectors (RFI Cable Group B)	RFA-4005-09
	.080", .100", .429" for RG-8/U, RG-11/U and RG-213/U (RFI Cable Group E)	RFA-4005-10
	Belden 9913, LMR <sup>®</sup> -400, WBC-400 (RFI Cable Group I); .429", .118" hex cavities	RFA-4005-14



All dies are available separately